


Last update on 2018-03-11 20:45. More details available at https://www.aqform.com/en/PR4016



AVAILABLE FINISHES:

STRUCTURE ADDITIONAL



Tolerance for dimensions $\pm\ 1\text{mm}$

Warranty period 5 years

2000 PRO LED track

2000 PRO LED track

Category: spotlights

Light source: LED, integrated

Dimming options: DALI Integrated light source

Gear included.

Adapter colour depends on the luminaire finish: white luminaire has a white adapter, other finishes have a black adapter. Appearance of the luminaire differs depending on the chosen

versior

Size of the radiator depends on the power of the luminaire. L power - L length = 85mm. M and H power - L length = 127mm.

DALI variants of the luminaire require DALI tracks. Adapters: standard or DALI..



AVAILABLE VERSIONS:

| H927 | High power - High power | 2700K | CRI>90 |
|------|-----------------------------|-------|--------|
| L927 | Low power - Low power | 2700K | CRI>90 |
| M927 | Medium power - Medium power | 2700K | CRI>90 |
| H930 | High power - High power | 3000K | CRI>90 |
| L930 | Low power - Low power | 3000K | CRI>90 |
| M930 | Medium power - Medium power | 3000K | CRI>90 |
| H940 | High power - High power | 4000K | CRI>90 |
| L940 | Low power - Low power | 4000K | CRI>90 |
| M940 | Medium power - Medium power | 4000K | CRI>90 |

AVAILABLE FINISHES:

STRUCTURE

| black structure | -12 | white structure | -13 |
|-----------------|-----|-----------------|-----|
| gold structure | -19 | | |
| ADDITIONAL | | | |
| grey | -16 | copper | -17 |